

# ZS-CO201

## Carbon Dioxide Sensor





## Carbon Dioxide Sensor

### ZS-CO201

The Zenosmart LoRaWAN CO2 Sensor Module detects carbon dioxide (CO<sub>2</sub>) levels in the surrounding air and transmits the data wirelessly. It is compatible with the LoRaWAN™ Class A protocol and can operate on battery or mains power. It is designed for air quality monitoring.

Carbon dioxide (CO<sub>2</sub>) is a colorless, odorless gas that is denser than air. It occurs naturally in the atmosphere and is released through processes such as respiration and combustion. However, at high concentrations, it can have adverse effects on health and the environment. You can safely use Zenosmart LoRaWAN CO<sub>2</sub> sensor modules to monitor CO<sub>2</sub> emissions.

<b>Communication Range</b>	2500m <sup>1</sup>
<b>Sensor Features</b>	CO2 Measurement Range: 0–2000 ppm
<b>Power</b>	3.6V 19000mAh
<b>Frequencies</b>	EU433 – KR920 – US915 /EU868 – AS923 – AU915
<b>Connections</b>	LoRaWAN <sup>1</sup>    <sup>2</sup>
<b>Monitoring</b>	Web and Mobile-Based Remote Monitoring
<b>Dimensions</b>	(H×W×D): 154 × 67 × 60 mm

1. The range may vary depending on the gateway antenna gain and geographic conditions.
2. Bluetooth is offered as an optional feature based on preference.



You can manage your CO<sub>2</sub> monitoring either through our web management platform at [zenosmart.com](https://zenosmart.com) or via your own servers

## Installation

Once the CO<sub>2</sub> sensor's battery is inserted, it immediately connects to the nearest LoRaWAN gateway and starts sending data to the IoT server. The operating temperature should be between -20°C and 60°C

## Usage

The device is fully waterproof (IP67 rated) and, when powered by a 3.6V 19Ah lithium battery, offers up to 10 years of battery life depending on usage